

M18 Fuel[™] Mid-Torque Impact Wrench with Pin Detent Kit

- · Pin detent locks sockets in place securely, especially while working overhead
- The PowerState[™] brushless motor delivers up to 550 ft-lbs. of max fastening torque
- 4-Mode Drive Control[™] provides greater control over output speed and power. Includes auto shut-off and bolt-removal control
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Works in up to to 69 kV environments
- 6.0" in length provides most access in tight spaces
- Tri-LEDs deliver high definition lighting to increase
- workspace visibility with less shadows
- Auto Shut-Off[™] control applies no more than 35 ft-lbs of torque for hand-tight fastening applications to prevent overtightening
- RedLink Plus[™] Intelligence ensures maximum performance and

1/2'

- protects from overloads, heating and over-discharge
- Compatible with all M18[™] batteries & chargers
- Includes: (1) M18 Fuel[™] 1/2" Mid-Torque Impact Wrench with Pin Detent (2962P-20), (2) M18[™] RedLithium[™] XC5.0 Resistant Battery (48-11-1850R), (1) M18[™] & M12[™] Multi-Voltage Charger (48-59-1812), (1) Blow Molded Case

SPECIFICATIONS

Voltage: Socket Size: **Battery Type:** Max Torque: No Load RPM: IPM:

Model No. UAV817 Mfg. No. 2962P-22R Price/Each \$



Milwaukee

M18 Fuel[™] Compact Impact Wrench with Friction Rina Kit

- 4.9" length provides most access in tight spaces
- The Powerstate[™] brushless motor delivers up to 250 ft-lbs. of nut-busting torque
- Tri-LEDs deliver high definition lighting to increase workspace visibility with less shadows
- 4-Mode Drive Control[™] provides greater control over output speed and power. Includes auto shut-off and bolt-removal mode
- Auto shut-off mode prevents over tightening and increases
- productivity by applying no more than 20 ft-lbs. of torque
- Bolt-removal mode offers more control after bolt breakaway as RPMs drastically slow down once the bolt is loosened
- Redlink Plus[™] Intelligence ensures maximum performance and protects from overloads, heating and over-discharge
- Works in up to to 69 kV environments
- Compatible with all M18[™] batteries & Chargers
- Includes: M18 Fuel[™] 1/2 " Compact impact wrench with friction ring (2855-20), (2) M18[™] Redlithium[™] XC5.0 Resistant batteries (48-11-1850R), (1) M18[™] & M12[™] Multi-voltage charger (48-59-1812), (1) Blow molded case

SPECIFICATIONS

Model No

UAK139

UAV745

•••••••••••••••••••••••••••••••••••••••	
Voltage:	18 V
Socket Size:	1/2"
Battery Type:	Lithium-lon
Max Torque:	250 ft-lbs
No Load RPM:	2400
IPM:	3500

Desc.

Tool Only

Tool & Kit

Price/Each

Mfg. No.

2855-20

2855-22R



Milwaukee

M18 Fuel[™] Utility High Torque Impact Wrench with One-Key[™] Kit

- Ergonomically designed for the lineman, providing you with superior control whether in-bucket, on-ground or climbing
- Designed with an extended handle to fit high voltage safety gloves for superior grip
 - Quik-Lok[™] technology enables one-handed bit insertion
 - One-Key[™] technology enables the user to customize, track and manage their tool
 - RedLink Plus[™] intelligence ensures maximum performance and
 - protects from overloads, heating and over-discharge
 - Includes: (1) M18[™] Fuel[™] Utility High Torque Impact Wrench with One-Key[™], (2) M18[™] Redlithium[™] XC5.0 Extended capacity battery pack, (1) M18[™] & M12[™] Multi-voltage charger, (1) Contractor Bag, (1) Inverter

SPECIFICATIONS

Voltage: Socket Size: **Battery Type:** Max Torque: No Load RPM:

18 V 7/16" Lithium-lon 750 ft-lbs 1300

Model No. UAF083 Mfg. No. 2865-22 Price/Each \$

Milwaukee



M18 Fuel[™] Mid-Torque Impact Wrench with Friction Rina Kit

- Friction ring (hog ring) ensures quick and easy socket changes
- Faster removal speed provides increased user productivity
- 4-Mode Drive Control[™] provides greater control over output speed and power, and includes auto shut-off and bolt-removal mode
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops Works in up to to 69 kV environments
- 6.0" in length provides most access in tight spaces Tri-LEDs deliver high definition lighting to increase
- workspace visibility with less shadows
- Auto Shut-Off™ control applies no more than 35 ft-lbs of torque for hand-tight fastening applications to prevent overtightening
- RedLink Plus[™] Intelligence ensures maximum performance and protects from overloads, heating and over-discharge
- Compatible with all M18[™] batteries & chargers
- Includes: (1) M18 Fuel[™] 1/2" Mid-Torque Impact Wrench with Friction Ring Kit (2962-22R), (2) M18[™] RedLithium[™] XC5.0 Resistant Battery (48-11-1850R), (1) M18[™] & M12[™] Multi-Voltage Charger (48-59-1812), (1) Blow Molded Case

SPECIFICATIONS Voltage:

Socket Size:

Battery Type:

Max Torque:

IPM:

No Load RPM:

18 V 1/2"

Lithium-lon 650 ft-lbs 2575 3100

Model No.	Mfg. No.	Desc.	Price/Each
UAK137	2962-20	Tool Only	
UAV816	2962-22R	Tool & Kit	



Milwaukee

www.tenaquip.com